Round Tubing	ID - Inner Diameter Range (inches)			OD - Outer Diameter Range (inches)			LG - Length (inches) ₁		
	0.008 - 1.999	2.000 - 4.249	4.250 - 6.500	0.010 - 1.999	2.000 - 4.249	4.250 - 6.500	Under 48.00 ₂	Over 48.00	ALL Tubes ≥ 4.25"
Roll Wrapped (includes Fabric, Unidirectional, Braided Overwrap,)	+/- 0.006	+/- 0.010	+/- 0.015	+/- 0.012	+/- 0.020	+/- 0.025	+/- 0.060	+/- 0.25	+/- 0.50
Pultruded Tubing & Solid Rods		NA	NA		NA	NA	+/- 0.25		NA
Camera Rails (15mm & 19mm) ₃	+/- 0.006	NA	NA	+/- 0.003	NA	NA			NA
Filament Wound (sanded)	+/- 0.007	+/- 0.010	+/- 0.015	+/- 0.012	+/- 0.015	NA	+/- 0.060	+/- 0.25	+/- 0.50
Filament Wound (unsanded)				+/- 0.040	+/- 0.050	+/- 0.060			+/- 0.30

Shaped Tubing ₄	ID - Inner Flat to Flat (inches)	OD - Outer Flat to Flat (inches)	LG - Length (inches)		
	0.250 - 2.000	0.750 - 2.250	Under 48.00 ₂	Over 48.00	ALL Tubes ≥ 4.25"
Square					
Rectangular	+/- 0.006	+/- 0.020	+/- 0.060	+/- 0.25	+/- 0.50
Hexagonal	+7-0.000	+/- 0.020	+/- 0.000	+/- 0.23	+/- 0.50
Octagonal					

Notes

- 1 Current saw capacity allows for cutting up to 4.0" diameter tubes, beyond 4.0" OD the tolerance defaults to +/- 0.50".
- 2 Tighter tolerances available under 48" for additional charge.
- 3 Nominal OD for the 15mm rails is 0.588" OR 14.94mm, Base size for the 19mm rails is 0.743" OR 18.87mm.
- 4 Radius of corners not called out Typically, radius is mentioned in the details for each SKU on the website. Tolerances here apply to all online products unless stated otherwise on product page.